

Depth Filtration

BECODISC® R+ Range

Extra Robust Premium Depth Filter Medium

BECODISC R+ stacked disc cartridges from Eaton are characterized by maximum purity. Through continuous product improvement, we have been able to improve the outstanding purity properties with even greater stability. Users can increase the filter service life considerably by backflushing. For backflushing a backflush set is not required.

Different types of high-purity cellulose are cross-linked in Eaton's innovative BECODISC R+ stacked disc cartridges to form a unique structure that does not require the addition of any inorganic material, even for super fine filtration.

The specific advantages of BECODISC R+ stacked disc cartridges:

- Increased service life due to possibility of backflushing
- Very high robustness due to the special design
- Optimized flow distribution upstream and downstream of the filter sheets maximizes filter utilization
- Combines all advantages of BECOPAD® filter material
- No use of an additional backflush set is required

Ingredients


BECODISC R+ stacked disc cartridges are made only of high-purity cellulose and wet strength agents and a special fabric spacer as drainage layer.

Areas of Application

BECODISC R+ stacked disc cartridges can be used for filtration of all liquid media. Application options range from coarse filtration to microbe removal.



Water throughput BECODISC R+ range



Conditions: Δ p = 100 kPa (1 bar), Medium: Water at 20 °C

Guide to choosing the right BECODISC R+ Stacked Disc Cartridge

B1C6

Fine colloids removal, especially for membrane protection

B176

Microbial removal filtration

B226, B276

Microbial reduction filtration

B356

Fine filtration, removal of yeasts

B456

Clarifying filtration



Powering Business Worldwide

Physical Data


This information is intended as a guideline for the selection of BECODISC R+ stacked disc cartridges. The water throughput is a laboratory value characterizing the different BECOPAD depth filter medium types. It is not the recommended flow rate.

Type*	BECOPAD depth filter sheet	Nominal retention range μm	Thickness in (mm)	Ash content %	Bursting strength wet psi (kPa**)	Water throughput at	
						$\Delta p = 14.5 \text{ psi}$ gpm/ft ²	$(\Delta p = 100 \text{ kPa}^{**})$ l/m ² /min)
B1C6	115 C	0.1 – 0.2	0.16 (4.1)	< 1	> 21.8 (150)	0.6	(26)
B176	170	0.2 – 0.4	0.15 (3.9)	< 1	> 21.8 (150)	1.9	(77)
B226	220	0.3 – 0.5	0.15 (3.9)	< 1	> 21.8 (150)	2.5	(100)
B276	270	0.5 – 0.7	0.15 (3.9)	< 1	> 21.8 (150)	3.3	(135)
B356	350	0.7 – 1.0	0.15 (3.9)	< 1	> 21.8 (150)	3.9	(160)
B456	450	1.0 – 2.0	0.15 (3.9)	< 1	> 21.8 (150)	7.4	(300)

*B = Polypropylene version (e.g. B1C6)

** 100 kPa = 1 bar

Ordering Information



¹ B1C6 with 16 cells only

Example: B17612SF

Backflushing polypropylene stacked disc cartridge with BECOPAD 115 C depth filter sheets, nominal retention range from 0.2 to 0.4 μm , 17 filter cells, 10.9 in (276 mm) high, 12", with silicone gaskets and flat adapter.

Compliance Notice

BECO depth filter sheets fulfill the requirements of Regulation (EC) 1935/2004 as well as the FDA Guideline 21 CFR § 177.2260 test criteria. The polypropylene components comply with Regulation (EU) 10/2011. The polypropylene meets FDA requirements, 21 CFR § 177.1520. The polyamide meets the requirements of FDA, 21 CFR § 177.1500. The sealing materials (silicone, EPDM) meet FDA requirements, 21 CFR § 177.2600. For further details on individual components and materials see the declaration of conformity.

Recommendations for Avoiding Damage

BECODISC R+ stacked disc cartridges can be used only in the specified flow direction. This applies to product filtering as well as sanitizing with hot water, and sterilizing with the stacked disc cartridges with saturated steam. Refer to the insert included with each BECODISC R+ stacked disc cartridge carton for detailed application information.

Depending on the filtered liquids, the operating temperature should not exceed 176 °F (80 °C). Please contact Eaton regarding filtration applications at higher temperatures.

Intermediate Plates

If more than one BECODISC R+ stacked disc cartridges (12" or 16") stacked in the housing, Eaton recommends the installation of stainless steel intermediate plates between the BECODISC R+ stacked disc cartridges.

Sanitizing and Sterilizing (Optional)

Sterilizing with Hot Water

The hot water temperature should be 185 °F (85 °C). A differential pressure of 21.8 psi (150 kPa, 1.5 bar) must not be exceeded when sterilizing with hot water.

Sterilization time: At least 30 minutes once a temperature of 185 °F (85 °C) is reached at all filter openings. In the interest of energy conservation, the water may be circulated provided the specified temperatures are maintained.

Sterilizing with Steam

The wetted BECODISC R+ stacked disc cartridges can be sterilized with saturated steam up to a maximum temperature of **250 °F (121 °C)** as follows:

- Steam quality: The steam must be free of foreign particles and impurities.
- Temperature: Max. **250 °F (121 °C)** (**saturated steam**)
- Duration: Approx. 20 minutes after steam exits from all filter valves
- Rinsing: After sterilizing with 0.61 gal/ft² (25 l/m²) at 1.25 times the flow rate

Filter Preparation and Filtration

Unless already completed after sterilization, rinse the stacked disc cartridges with 0.61 gal/ft² (25 l/m²) of water at 1.25 times the flow rate prior to the first filtration. Check the entire filter for leakage at maximum operating pressure.

High-proof alcoholic solutions and products that cannot be rinsed with water should be circulated with the product. Discard the rinsing solution after rinsing.

Differential Pressure

Terminate the filtration process once the maximum permitted differential pressure of 43.5 psi (300 kPa, 3 bar) is reached. A higher differential pressure could damage the depth filter sheet material. For safety reasons, a differential pressure of 21.8 psi (150 kPa, 1.5 bar) should not be exceeded in applications for separating microorganisms.

Rinsing the Filter

BECODISC R+ stacked disc cartridges can be operated against the direction of flow for regeneration purposes. This applies for regenerating with cold and hot water.

The maximum permissible differential pressure for backwashing is 7.25 psi (50 kPa, 0.5 bar) at 50 to 185 °F (10 to 85 °C).

Safety

When used and handled correctly, there are no known unfavorable effects associated with this product.

Further safety information can be found in the relevant Material Safety Data Sheet, which can be downloaded from our website.

Disposal

Due to their composition, BECODISC R+ stacked disc cartridges can be disposed of as harmless waste. Comply with relevant current regulations, depending on the filtered product.

Storage

BECODISC R+ stacked disc cartridges must be stored in a dry, odor-free, and well ventilated place.

Do not expose the BECODISC R+ stacked disc cartridges to direct sunlight.

BECODISC R+ stacked disc cartridges are intended for immediate use and should be used within 36 months after production date.

Delivery Information

BECODISC R+ stacked disc cartridges are available with 17 cells, 12-inch (295 mm, 2.1 m²) and 16-inch (402 mm, 4 m²) diameters, flat adapters, and standard silicone gaskets.

Quality Assurance According to DIN EN ISO 9001

The Quality Management System of Eaton Technologies GmbH has been certified according to DIN EN ISO 9001.

This certification verifies that a fully functioning comprehensive Quality Assurance System covering product development, contract controls, choice of suppliers, receiving inspections, production, final inspection, inventory management, and shipment has been implemented.

Extensive quality assurance measures incorporate adherence to technical function criteria and chemical purity and quality recognized as safe under the German legislation governing the production of foods and beverages.

All information is given to the best of our knowledge. However, the validity of the information cannot be guaranteed for every application, working practice and operating condition. Misuse of the product will result in all warranties being voided.

Subject to change in the interest of technical progress.

North America
44 Apple Street
Tinton Falls, NJ 07724
Toll Free: 800 656-3344
(North America only)
Tel: +1 732 212-4700

Europe/Africa/Middle East
Auf der Heide 2
53947 Nettersheim, Germany
Tel: +49 2486 809-0

Friedensstraße 41
68804 Altlufzheim, Germany
Tel: +49 6205 2094-0

An den Nahewiesen 24
55450 Langenlonsheim, Germany
Tel: +49 6704 204-0

China
No. 3, Lane 280,
Linhong Road
Changning District, 200335
Shanghai, P.R. China
Tel: +86 21 5200-0099

Singapore
100G Pasir Panjang Road #07-08
Singapore 118523
Tel: +65 6825-1668

Brazil
Rua Clark, 2061 - Macuco
13279-400 - Valinhos, Brazil
Tel: +55 11 3616-8400

**For more information, please
email us at filtration@eaton.com
or visit www.eaton.com/filtration**

EN
1A255:18
08-2018

© 2018 Eaton. All rights reserved. All trademarks and registered trademarks are the property of their respective owners. All information and recommendations appearing in this brochure concerning the use of products described herein are based on tests believed to be reliable. However, it is the user's responsibility to determine the suitability for his own use of such products. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Eaton as to the effects of such use or the results to be obtained. Eaton assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete, since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations.